

CobraMig[®] 350P

PULSE ALUMINUM PUSH-PULL MIG WELDER SYSTEM

Introducing the CobraMig®350P by MK Products®. Specifically designed for aluminum. Nearly everything you need to start welding—just add your 10-pin MK compatible push-pull torch.

Packages come complete with:

- CobraMig®350P Controller
- CobraMig®350P Wire Feeder
- CobraMig®350P Power Supply
- CobraCooler®55 (Water Cooled Package Only)
- Integrated Cart
- Cobra®Coolant (2gal./9L) (Water Cooled Package Only)
- 15FT Weld Ground Cable with Clamp
- Flowmeter Regulator Kit with 10FT Gas Hose

CobraMig®350P CONTROLLER

- ◆ Power in your hands up to 50 feet away from your system

CobraMig® 350P FEEDER

- ◆ Wire Sizes: .030"–1/16" Aluminum Wire
- ◆ 12" Diameter Spool or Bulk Wire Drum
Using Optional Adapter Kit
- ◆ Power Input: 115VAC 50-60 Hz
- ◆ Gun Compatibility:
All 10Pin, MK Compatible Push-Pull Torches

CobraMig®350P POWER SUPPLY

- ◆ Power Input: 460-575VAC 3 Phase 50-60 Hz
- ◆ Welding Current Output: 350A @ 60% Duty Cycle

CobraCooler®55

- Power Input: 115VAC 1 Phase 50 Hz
Reservoir Capacity: Approximately 2gal./9L
Coolant Type: Use Cobra®Coolant to protect aluminum, copper, and brass; contains no sulfur or chlorine
Maximum System Pressure is 60 PSI

Available Separately

- 15', 25', 35', 50' MIG 10-Pin Push-Pull Torch-Python®, Prince®XL, Cobra®MX, Cobra®MX-HD
CobraMig®350P Wire Feeder Umbilical Extension Cables
CobraMig®350P Controller Extension Cables

MIG WELDING SYSTEMS



MIGTM
PUSH-PULL SYSTEMS

MK Products, Inc.
16882 Armstrong Avenue, Irvine, CA 92606

Tec Welding Products, Inc.
500 S. Andreasen Drive, Suite 100, Escondido, CA 92029

Tec Welding Products, Inc.
8248 NW 101st. Terrace, Unit 1, Kansas City, MO 64153

800-787-9707
sales@mkprod.com • mkprod.com

Scan for more product offerings
and company information



All brands are registered trademarks of MK Products, Inc. ♦ 091-0812-032026-Rev. A



MK
PRODUCTS

MADE IN

U S A

Python®

AIR/WATER COOLED MODELS

♦ The industry's most advanced aluminum push-pull gun

♦ Key Features:

- EZ-Lock® barrel with 360° rotation
- Forward trigger operation
- Ultra-Flex power cable

♦ Specs:

- Wire sizes
•.030"-1/16"
(0.8mm-1.6mm) aluminum wire
•.030"-.045"
(0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty Cycle - 100%
225 AMPS - Air
400 AMPS - Water



Python

♦ The industry's most advanced aluminum push-pull gun

♦ Key Features:

- EZ-Lock® barrel with 360° rotation
- Rear trigger operation
- Integrated mechanical gas valve ensures precise control of shielding gas
- Ultra-Flex power cable

♦ Specs:

- Wire sizes
•.030"-1/16"
(0.8mm-1.6mm) aluminum wire
•.030"-.045"
(0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty Cycle - 100%
225 AMPS - Air
400 AMPS - Water



Python^{LX}

♦ Compatible wherever Miller® AlumaPro™Plus is used

♦ Key Features:

- EZ-Lock® barrel with 360° rotation
- Forward trigger operation
- Ultra-Flex power cable

♦ Specs:

- Wire sizes
•.030"-1/16"
(0.8mm-1.6mm) aluminum wire
•.030"-.045"
(0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty cycle - 100%
225 AMPS - Air
400 AMPS - Water



Python^{ProPlus}

Available in lengths of 15', 25', 35', 50'

CobraTurn® T-260

- ♦ Tabletop de-clutch release
- ♦ Weld ground fault protection
- ♦ Digital RPM control
- ♦ Linear single speed control knob with center push button start, stop and jog functions
- ♦ Gas ID purge through center shaft
- ♦ High frequency interference protection
- ♦ Appropriate for all welding applications
- ♦ Includes 10" tabletop and on/off foot switch
- ♦ Specs:
- Balanced Load Capacity: 260lbs. Horizontal and 130lbs. Vertical & Centered 7" Max from the table
- Degree Tilt: 0°-90° in 15° increments
- Speed Range R.P.M.: 0.1 - 6
- Ground Capacity AMPS: 400A 60% Duty Cycle
- Input Voltage: 120 VAC 50/60 Hz
- Shipping Weight: 38lbs.



CobraTurn® T-30

- ♦ Compact high performance turntable
- ♦ Weld ground fault protection
- ♦ Adjustable LED illuminated control panel
- ♦ Linear single speed control knob with center push-button start, stop and jog functions
- ♦ Cam lever to lock table angle
- ♦ High frequency interference protection
- ♦ Includes 5" tabletop and on/off foot switch
- ♦ Specs:
- Balanced Load Capacity: 30lbs. Horizontal and 15lbs. Vertical
- Degree Tilt: 0°-90°
- Speed Range R.P.M.: 0.4 - 6
- Ground Capacity AMPS: 400A 60% Duty Cycle
- Input Voltage: 120 VAC 50/60 Hz
- Shipping Weight: 14lbs.



♦ Both available with optional Heavy Duty Variable Speed Foot Control and a Self-Centering 3-Jaw Chuck

Cobra®

AIR/WATER COOLED MODELS

♦ Famous gooseneck design and lightweight build
For use with 1/4" consumables

♦ Key Features:

- Cobra® fixed gooseneck design with high-temp barrel insulator
- Integrated mechanical gas valve
- Rear trigger operation
- Ultra-Flex power cable

♦ Specs:

- Wire sizes
•.030"-1/16"
(0.8mm-1.6mm) aluminum wire
•.030"-.045"
(0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty Cycle - 100%
175 AMPS - Air
225 AMPS - Water



Cobra^{MX}

♦ Famous gooseneck design and lightweight build
For use with 3/8" consumables

♦ Key Features:

- Cobra® fixed gooseneck design with high-temp barrel insulator
- Integrated mechanical gas valve
- Rear trigger operation
- Ultra-Flex power cable

♦ Specs:

- Wire sizes
•.030"-1/16"
(0.8mm-1.6mm) aluminum wire
•.030"-.045"
(0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty Cycle - 100%
200 AMPS - Air
250 AMPS - Water



Cobra^{MXHD}

♦ Our lightest, smallest push-pull gooseneck

♦ Key Features:

- Cobra® fixed gooseneck design with high-temp barrel insulator
- Rear trigger operation
- Ultra-Flex power cable

♦ Specs:

- Wire sizes:
•.030"-.035" (0.8mm-9mm) aluminum wire
•.023"-.035" (0.6mm-0.9mm) steel, stainless steel, flux core
- Wire Speed:
0-800 IPM
- Duty Cycle - 100%
175 AMPS - Air



Cobra^{SX}

Available in lengths of 15', 25', 35', 50'

Contact Tips

3/8" ALUMINUM CONTACT TIP

For aluminum wire
Sold in 25 packs



3/8" SPRING LOADED CONTACT TIP

For aluminum wire
Sold individually



SUPERIOR ARC CONTROL

3/8" HARD WIRE CONTACT TIP

For steel, stainless steel and flux core wire
Sold in 25 packs



1/4" ALUMINUM CONTACT TIP

For aluminum wire
Sold in 25 packs



1/4" HARD WIRE CONTACT TIP

For steel, stainless steel and flux core wire
Sold in 25 packs



For Cobra® X, Cobra® MX, Cobra® Gold models

Prince®XL

AIR/WATER COOLED MODELS

♦ The most versatile pistol grip gun

♦ Key Features:

- EZ-Lock® barrel with 360° rotation
- Integrated mechanical gas valve
- Wire feed adjustment protected in the bottom of the handle
- Ultra-Flex power cable

♦ Specs:

- Wire sizes: .030"-1/16" (0.8mm-1.6mm) aluminum wire
.030"-.045" (0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed: 0-800 IPM
- Duty Cycle - 100%
225 AMPS - Air
400 AMPS - Water



Prince^{XL}



Prince^{XL}

Prince®XL

AIR COOLED SPOOL GUN

Available in lengths of 25', 50'

♦ The most powerful and versatile pistol grip spool gun

♦ Key Features:

- EZ-Lock® barrel with 360° rotation
- Wire feed adjustment protected in the bottom of the handle
- Ultra-Flex power cable

♦ Specs:

- Wire sizes: .030"-1/16" (0.8mm-1.6mm) aluminum wire
.030"-.045" (0.8mm-1.2mm) steel, stainless steel, flux core
- Wire Speed: 0-800 IPM
- Spool Size - 1lb. & 2lb. spools
- Duty Cycle - 100%
225 AMPS - Air



Prince^{XL}

Sidewinder®

AIR COOLED MINI SPOOL GUN

Available in lengths of 15', 25'

♦ Intended for applications with limited access, weight requirements or the need for a small footprint

♦ Extended reach 7" barrel for getting down in to deep spaces

♦ Combine with SP control modules to connect to small inverters or portable engine-driven power sources.

♦ Specs:

- Wire sizes: .030"-.035" (0.8mm-0.9mm) aluminum wire
Mini Spool 1/4lb. welding wire is required for this gun
- Wire Speed: 0-600 IPM
- Spool Size - 1/4lb. spools
- Duty Cycle - 60%
135 AMPS - Air



Sidewinder®